



D1T Supergrip Readymix Adhesive

Showerproof, High Yield, Ready Mixed Adhesive for Ceramic, Mosaic & Porcelain Wall Tiles, 13kg

2-3mm Bed Thickness / 15 mins Open Time / 24 hours Set Time

- Ceramics / Mosaics / Porcelain
- Plaster / Boards / Blockwork
- High Initial Grab / Non Slip
- Showerproof / High Yield
- Commercial / Domestic
- Interior Use

DESCRIPTION

ROCATEX D1T Supergrip Readymix Adhesive offers high initial grab, ease of application and excellent non-slip properties. It is an off-white, polymer based, thin bed tile adhesive suitable for fixing ceramic, mosaic and porcelain wall tiles in internal locations such as bathrooms, kitchens and domestic shower areas (when used with a waterproof grout). Conforms to BS EN 12004 D1T and can be applied to gypsum plaster, plasterboard, tile backer board, cement and gypsum fibreboard, existing tiles, cement render and concrete blockwork. Not suitable for wetrooms or swimming pools. Interior use only.

PREPARATION & PRIMING

All surfaces must be clean, firm and free of dust, dirt, oil, grease and loose flaking coatings. The surface must also be sufficiently flat not to require an adhesive thickness greater than 3mm. Gypsum finishing plaster should be at least 4 to 6 weeks old, thoroughly dry and be free from dust, efflorescence and loose flaking material. Highly polished (shiny) plaster surfaces should be roughened with a wire brush, removing all loose fines. Remove areas of unsound paint from walls (emulsion paints are not suitable and must be removed). All porous surfaces should be primed with 1 diluted coat (1 part primer mixed with 1 part clean water) of ROCATEX Acrylic Primer or ROCATEX Ultimate Grip Primer and allowed to dry. Existing tiles and other non-porous substrates should be primed with 1 neat coat of ROCATEX Ultimate Grip Primer and allowed to dry. Expansion joints should be installed in accordance with the recommendations of BS 5385.

APPLICATION

ROCATEX D1T Supergrip Readymix Adhesive should be applied with a 6mm notched trowel to give a ribbed bed on the wall surface, into which the tiles are firmly bedded with a twist and slide action to ensure complete contact. The position of the tiles can be adjusted up to 10 minutes after initial fixing. Open time of the exposed adhesive bed is approximately 15 minutes depending on surface porosity and site conditions, however, in warm rooms this period may be reduced - check the adhesive remains "tacky to touch" as fixing proceeds. Do not trowel out an area of adhesive greater than can be tiled over within a 10 minute period (about 1m²).

The final adhesive bed depth should be in the range of 2 - 3mm and grout joints should be at least 2mm. Ensure all adhesive residues remaining on the tile face are wiped clean with a damp cloth as fixing proceeds, and rake out any excess adhesive from within the grout joints. ROCATEX D1T Supergrip Readymix Adhesive should not be applied onto walls affected by penetrating damp, in areas of persistently high humidity or when the room temperature is below 5°C. This product should not be used for fixing tiles with dimensions greater than 300 x 300mm (or equivalent surface area) - a cement based alternative such as ROCATEX C2TE S1 Slow Flex White should be used.

ROCATEX

Rocatex Ltd
3+4 Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com

This information is offered without guarantee. Our Company policy is one of continuous research and development, we therefore reserve the right to update this information at any time without prior notice. We guarantee the consistent high quality of our products, however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. If in doubt, conduct a small test or obtain further technical advice.

GROUTING

Grouting may proceed as soon as the tile bed is sufficiently firm, which depending upon site conditions can be from 24 hours after fixing on porous surfaces such as plaster, or up to 7 days where tiles have been fixed to an impermeable surface such as existing tiles or waterproof boards. These periods however may be prolonged in cold conditions. In areas subject to intermittent wetting, such as domestic showers, always use a waterproof grout such as ROCATEX CG2 WA Ultimate Grout. Allow up to 14 days for both the adhesive and grout to fully dry out before subjecting the tiled area to contact with water.

COVERAGE

Depending on surface texture and porosity, on a typical smooth plastered wall ROCATEX D1T Supergrip Readymix Adhesive will cover at a rate of 1 - 2kg per m². Coverage is dependent on the application technique, substrate and type of tiles used and these figures are therefore a guide only.

STORAGE

When stored unopened in a dry place at temperatures between 5°C - 30°C, shelf life is 12 months from date of manufacture.

TECHNICAL DATA

Conformity:	Conforms to the requirements of BS EN 12004 D1T
Application temperature:	5°C to 25°C
Bed thickness:	2-3mm
Open time:	15 mins at 20°C subject to substrate
Set time:	24 hrs at 20°C subject to substrate
Ready for grouting:	24 hrs at 20°C porous substrate, up to 7 days non-porous substrate
Shelf life:	12 months in cool dry area
Sizes:	13kg

CE		
Rocatex Ltd, Units 3+4 Camwal Park, Camwal Road, Harrogate, HG1 4PT, UK 19 DoP No. 010 EN 12004		
Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire (class)	Class F	EN 13501-1:2007+A1:2009
Initial shear adhesion strength (declared)	≥ 1,0 N/mm ²	EN 12004-1:2007+A1:2012
Durability of bond strength against climate/heat ageing action expressed as: - shear adhesion strength after heat ageing	≥ 1,0 N/mm ²	EN 12004-1:2007+A1:2012
Release of dangerous substances	See SDS	EN 12004-1:2007+A1:2012

HEALTH & SAFETY INSTRUCTIONS

Avoid skin and eye contact. Handle only when wearing protective clothing. Wash splashes from skin with soap and water. Flush eyes with copious amounts of water and seek medical attention if irritation persists.